

DU-1481-7

Direct-drive, 1-needle, Top and Bottom-feed, Lockstitch Machine with Double-capacity Hook with Automatic Thread Trimmer



High long arm sewing machine with automatic thread trimmer











Direct-drive, 1-needle, Top and Bottom-feed, Lockstitch Machine with Double-capacity Hook

DU-1481-7



HOTLINE: 0982 085 899

Needle thread clamping device

The needle thread device is standard equipment. As a result, the needle thread at the start of sewing does not come out on the cloth, so the start of sewing beautiful finished seams.

Operators use scissors less often and can preven

Operators use scissors less often and can prevent damage to the material caused by thread picking.

Direct-drive motor is installed

The direct-drive motor system has been adopted by all of the sewing system with a thread trimmer. As a result, the sewing machine starts up swiftly and promises increased stop accuracy, thereby demonstrating improved responsiveness.



Increased productivity by improved operability

The machine achieves a longer distance from machine arm to needle by adopting a high long arm.

This means the machine dramatically increases workability when sewing large products such as sofas and car seats.

The adoption of the alternating vertical movement control dial enables easy adjustment of the amount of the alternating vertical movement of the walking foot and presser foot without requiring any tool.



The presser bar lifting lever is located on the front surface of the sewing machine to achieve ease of operation.

The DU-1481-7 is suited to the sewing and decorative shape-tacking of heavy-weight materials such as car seats, sofas, bags and stroller.

Feature

LED Light

Standard equipped with LED light to illuminate the hand of the needle. The operator can set the brightness which is easy to work, improving work efficiency.

Feed mechanism

The machine's powerful top & bottom feed demonstrates its performance when sewing car fabric seats. The lift of the presser foot is as high as 16 mm, which responds to the sewing of heavy-weight materials.

Horizontal-axis full-rotary double-capacity hook

The adoption of the horizontal-axis double-capacity hook helps reduce the frequency of bobbin thread replacement, thereby promising sewing work with efficiency. This hook is also helpful not only when sewing with thick thread but also when sewing a long seam length.

Mechanism of thread trimmer

The thread trimmer achieves consistent thread trimming regardless of thickness of the thread, i.e., from thin to thick thread. The machine has adopted the rotary thread trimming mechanism which matches, in particular, design stitch with thick thread for furniture and bags. The automatic thread trimmer improves workability and increases productivity. When compared with the sewing machine without a thread trimmer, the DU-1481-7 substantially decreases the consumption of thread. The knife pressure can be adjusted with the adjusting screw.



SPECIFICATIONS [Model DU-1481

Max. sewing speed	2,200sti/min	
Max. stitch length	9:nm (forward / backward)	
Needle bar stroke	38 ^t nm	
Lift of the presser foot	By hand: 7mm, By knee: 16mm	
Thread take-up	Link type	
Alternating vertical movement	2~5.5mm	
Hook	Horizontal-axis full-rotary double-capacity hook	
Needle	DPx17 #23 (#18~#24)	

Thread	#20~#8
Pitch changing method	By dia
Lubrication	Automatic
Lubricating oil	MACHINE OIL No.18 (ISO VG18 equivalent)
Distance from needle to machine arm	335mm×150mm
Weight of the machine head	37kg
	*sti/min stands for "Stitches per Minute."

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

Head DU1481 085 899 ower supply Single-phase 100-120V 3-phase 200~240V D Κ Single-phase 200~240V

Single-phase 200~240V (for ce)

N

JUKI ECO PRODUCTS The DU-1481-7 is an eco-friendly product which complies with JUKI ECO PRODUCTS standards for protecting the environment.



• The sewing machine complies with the "Juki Group Green Procurement Guidelines" on the use of hazardous substances, which is stricter than other restrictions, such as those of the RoHS Directive.

For details of JUKI ECO PRODUCTS, refer to: http://www.juki.co.jp/eco_e/index.html

The RoHS Directive is an EU Directive limiting the use of 6 hazardous substances (lead, hexavalent chromium, mercury, cadmium, PBB and PBDE) in electrical and electronic equipment. The Juki Green Procurement Guideline is the voluntarily established criteria to eliminate not only the aforementioned six substances, but also other ones which also adversely affect the en







ered Organization: JUKI CORPORATION Head Officepe of the Registration: The activities of rese



SEWING MACHINERY & SYSTEMS BUSINESS UNIT

2-11-1, TSURUMAKI, TAMA-SHI, TOKYO 206-8551, JAPAN PHONE: (81) 42-357-2383 FAX: (81) 42-357-2274

http://www.juki.com

* Specifications and appearance are subject to change without prior notice for improvement.

- * Read the instruction manual before putting the machine into service to ensure safety.
- * This catalogue prints with environment-friendly soyink on recycle paper.
- * Paper from responsible sources FSC™ C001712